

Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate						Certificate No.	<b>011-7S1889 R</b>				
						Date of issue	29.05.2012				
Company	Ritter Energie- & Umwelttechnik GmbH & Co					Country	Germany				
Brand (optional)						Website	<a href="http://www.ritter-gruppe.com">www.ritter-gruppe.com</a>				
Street, number	Kuchenäckerstraße 2					E-mail	<a href="mailto:T.Weidemann@ritter-gruppe.com">T.Weidemann@ritter-gruppe.com</a>				
Postal Code	72135					Tel.	+49	(0)7202 922 134			
City	Dettenhausen					Fax	+49	(0)7202 922 100			
Collector Type (flat plate / evacuate tubular / un-glazed)						Evacuated tubular collector					
Integration in the roof possible ?						No					
Collector name	Aperture area (Aa)	Gross length	Gross width	Gross height	Gross area (Ag)	Power output per collector unit G = 1000 W/m <sup>2</sup> Tm-Ta :					
	[m <sup>2</sup> ]	[mm]	[mm]	[mm]	[m <sup>2</sup> ]	0 K	10 K	30 K	50 K	70 K	
AQUA PLASMA 19/17 *	1.49	2,058	823	110	1.69	1,024	1,014	992	967	938	
AQUA PLASMA 19/34 *	3.00	2,058	1,628	110	3.35	2,061	2,042	1,998	1,947	1,888	
AQUA PLASMA 19/50 *	4.50	2,058	2,433	110	5.01	3,092	3,063	2,997	2,920	2,832	
Collector efficiency parameters related to aperture area (Aa)						η <sub>0a</sub>	0.687		-		
Type of fluid and flow rate see note 1						a <sub>1a</sub>	0.613		W/(m <sup>2</sup> K)		
						a <sub>2a</sub>	0.003		W/(m <sup>2</sup> K <sup>2</sup> )		
Stagnation temperature - Weather conditions see note 2						t <sub>stg</sub>	338		°C		
Effective thermal capacity						C <sub>eff</sub> = C/Aa	8.78		kJ/(m <sup>2</sup> K)		
Max. operation pressure - see note 3						p <sub>max</sub>	1000		kPa		
Incidence angle modifiers K <sub>θ</sub> (θ)	G <sub>DIF</sub> /G <sub>TOT</sub>		θ <sub>T</sub> / θ <sub>L</sub>	50°	10°	20°	30°	40°	60°	70°	
	min	max	K <sub>θ</sub> (θ <sub>T</sub> )	0.96	1.01	1.02	1.02	1.02	1.06	1.20	
G <sub>DIF</sub> /G <sub>TOT</sub> : min&max - while measuring											
						<b>Optional values</b>					
Testing Laboratory						TZS, ITW University of Stuttgart					
Website						<a href="http://www.tzs.uni-stuttgart.de">www.tzs.uni-stuttgart.de</a>					
Test report id. number						11COL1008/1, 11COL1007/1, 11COL1007Q/1					
Date of test report						29.05.2012					
Perf. test method						EN 12975-2 6.1.4 (outdoor)					
Comments of testing laboratory :											
* dimensions according to manufacturer											
Note 1	Fluid	Water		Flow rate	0.020 kg/s per m <sup>2</sup>						
Note 2	Irradiance, G <sub>s</sub> =1000 W/m <sup>2</sup>										
Note 2	Ambient temperature, T <sub>a</sub> =30 °C										
Note 3	Given by manufacturer										

VERSION 3.6, 2012.01.13

DIN CERTCO • Alboinstraße 56 • 12103 Berlin

 Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: [info@dincertco.de](mailto:info@dincertco.de) • [www.dincertco.de](http://www.dincertco.de)



**Annual collector output based on EN 12975 Test Results,  
annex to Solar KEYMARK Certificate**

**Certificate No.** 011-7S1889 R  
Issued 29.05.2012

Annual collector output kWh												
Location and collector temperature (T <sub>m</sub> )												
Collector name	Athens			Davos			Stockholm			Würzburg		
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
AQUA PLASMA 19/17 *	1,768	1,664	1,544	1,659	1,551	1,430	1,128	1,032	934	1,207	1,106	1,001
AQUA PLASMA 19/34 *	3,560	3,350	3,109	3,340	3,123	2,879	2,271	2,078	1,881	2,430	2,227	2,015
AQUA PLASMA 19/50 *	5,340	5,026	4,663	5,010	4,684	4,319	3,407	3,117	2,821	3,645	3,340	3,023

Collector mounting: Fixed or tracking Fixed; slope = latitude - 15° (rounded to nearest 5°)

Overview of locations				
Location	Latitude °	Gtot kWh/m <sup>2</sup>	Ta °C	Collector orientation or tracking mode
Athens	38	1,765	18.5	South, 25°
Davos	47	1,714	3.2	South, 30°
Stockholm	59	1,166	7.5	South, 45°
Würzburg	50	1,244	9.0	South, 35°

Gtot	Annual total irradiation on collector plane	kWh/m <sup>2</sup>
Ta	Mean annual ambient air temperature	°C
Tm	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

Calculation of the annual collector performance is done by the official Solar Keymark spreadsheet tool. Hour by hour the collector output is calculated according to the efficiency parameters from the Keymark test using constant collector operating temperature (T<sub>m</sub>). Detailed description with all equations used is available from the Solar Keymark web site (direct link: <http://www.estif.org/solarkeymark/annexb1.php>)

<p><b>DIN CERTCO • Alboinstraße 56 • 12103 Berlin</b>          Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: <a href="mailto:info@dincertco.de">info@dincertco.de</a> • <a href="http://www.dincertco.de">www.dincertco.de</a></p>	Datasheet version:
	VERSION 3.6, 2012.01.13
	Calculation program version:
	3.07, October 2011 (SP)